



The Specials are based on the standard reefer containers but specially adapted, the bespoke options are endless. Reftrade have a range of design engineers that can fit out containers to any size, specification and various types of equipment from Carrier to ATEX Zone 1. Available for Lease, lease/purchase & purchase.

They can be equipped with, an easy-to-open 'butcher-door' (both container doors can still be opened in the original way) or side entry doors.



220-series



221-series



222-series

Standard specifications:

- Aluminium flat floor (anti-skid)
- Internal lighting (min. 100 lux)
- Double container doors with easy to open butcher-door
- Man-trap release
- Chill curtain
- Stainless-steel inside lining

Options (ref brochure OPTIONS):

- Ramp (cap. 1.000kg.)
- Legs for load-dock connection
- Door lock
- Temperature alarm/Remote monitoring
- Machinery, extra powerful (-40°C)
- Racks (H.A.C.C.P.)
- Man-trap alarm
- Emergency stop & equipment shut off

Technical specifications:

Machinery	Electrical system	Connection	Cable	Cool / freeze capacity	Temperature range
CARRIER or THERMO KING	380/460V 50/60 Hz. 5-polig (3 Fase, Earth, zero)	32 Amp. 6hr. 380/460 V Fuse: 25 Amp.	minimum 15 meters	@ -18°C 4,9 - 6,6 kW @ +2°C 9,4 - 12 kW	CARRIER: -25°C / +25°C < 38°C Ambient THERMO KING: -40°C / +40°C < 38°C Ambient

Model	Loading capacity (Euro pallets)	Internal dimensions (l. x w. x h.) in mm. below load line	External dimensions (l. x w. x h.) in mm.	Door opening (w. x h.) in mm.	Floor surface	Capacity
10S	4	2,35 X 2,25 X 2,26 M.	2,99 X 2,44 X 2,59 M.	2,26 X 2,20 M.	5 M ²	12 M ³
20S	10	5,45 X 2,25 X 2,26 M.	6,06 X 2,44 X 2,59 M.	2,26 X 2,20 M. 1,90 X 2,14 M. (222-serie)	12 M ²	28 M ³
40S	23	11,53 X 2,25 X 2,26 M.	12,19 X 2,44 X 2,59 M.	2,26 X 2,20 M.	26 M ²	59 M ³
40SH	23	11,53 X 2,25 X 2,59 M.	12,19 X 2,44 X 2,89 M.	1,90 X 2,44 M.	26 M ²	67 M ³

