



**The Super Volumes**, based on the Volumes, offer the perfect solution for your (semi-)permanent cold storage issues with their width of 3.5m. These units are equipped with a Carrier or Thermo King machinery and are available in four types, the 20SV, 30SV, 40SV and the 48SV for 16, 26, 37 and 45 euro pallet capacity, respectively.



**Standard specifications:**

- Anti-skid Resin Flooring
- Internal lighting (min. 100 lux)
- Double container doors with easy to open butcher-door
- Man-trap release + Alarm
- Chill curtain
- Internal Height of 2700mm.

**Options (ref brochure OPTIONS):**

- Ramp (cap. 1.000kg.)
- Legs for load-dock connection
- Door lock
- Temperature alarm/Remote monitoring
- Racks (H.A.C.C.P.)
- Side Doors, Sliding Doors, Sectional Doors

**Technical specifications:**

Machinery	Electrical system	Connection	Cable	Cool / freeze capacity	Temperature range
CARRIER or THERMO KING	380/460V 50/60 Hz. 5-polig (3 Fase, Earth, zero)	32 Amp. 6hr. 380/460 V Fuse: 25 Amp.	minimum 15 meters	@ -18°C 4,9 - 6,6 kW @ +2°C 9,4 - 12 kW	CARRIER: -25°C / +25°C < 38°C Ambient THERMO KING: -40°C / +40°C < 38°C Ambient

Model	Loading capacity (Euro pallets)	Internal dimensions (l. x w. x h.) in mm. below load line	External dimensions (l. x w. x h.) in mm.	Door opening (w. x h.) in mm.	Floor surface	Capacity
<b>20SV</b>	16	5,26 X 3,34 X 2,70 M.	6,06 X 3,50 X 3,03 M.	2,03 X 2,63 M.	18 M <sup>2</sup>	48 M <sup>3</sup>
<b>30SV</b>	26	8,34 X 3,34 X 2,70 M.	9,14 X 3,50 X 3,03 M.	2,03 X 2,63 M.	28 M <sup>2</sup>	75 M <sup>3</sup>
<b>40SV</b>	37	11,39 X 3,34 X 2,70 M.	12,19 X 3,50 X 3,03 M.	2,03 X 2,63 M.	38 M <sup>2</sup>	104 M <sup>3</sup>
<b>48SV</b>	45	13,77 X 3,34 X 2,70 M.	14,63 X 3,50 X 3,03 M.	2,03 X 2,63 M.	45 M <sup>2</sup>	125 M <sup>3</sup>

